


S265N36BPV S270N36BPV S275N36BPV S280N36BPV

Shinson is a leading professional supplier in the renewable energy industry, specializing in the production and distribution of high-quality PV modules, completed PV kits, and energy storage solutions. With a commitment to sustainable energy solutions, we strive to provide innovative and reliable products to meet the growing global demand for clean and efficient power generation.

With a focus on quality, innovation, and customer satisfaction, we strive to empower individuals, businesses, and communities with reliable and sustainable energy solutions. By harnessing the power of the sun and embracing renewable energy, we are driving the transition towards a greener and more sustainable future.

S-Blade™ series of PV modules are designed with the idea of BIPV, can be widely used for buildings, roof-tops, solar fences and agriculture fields. The high transparency with bifacial design gives basic sunshine but with renewable energy generated.



High transparency , high efficiency

The optimized number and width of main gate lines, ensure the sunlight can go through and high efficiency of cells maximize the power generation.



Half-Cut Cell design

Half cut cell technology can reduce the internal power loss and improve the output power. Excellent heat dissipation avoids hot spot production



Longer life span with 30 years warranty

Shinson extended the warranty period up to 30 years for both performance and workmanship which is on top level of the industry for bifacial double glassed modules.



Lower power degradation with more generation

Ensured PID resistance through cell process and module material control to help harvest more, guaranteed only 0.4% annual power degradation .

S.blade™

BIPV Frameless

280W


Maximum Output Power

72

TOPcon Bifacial Cells

30~40%

Transmittance



Electrical Data (STC)

Part Number	S265N36BPV	S270N36BPV	S275N36BPV	S280N36BPV
Peak Power Watts- $P_{MAX}(Wp)^*$	265	270	275	280
Power Output Tolerance	0/+5W			
Open Circuit Voltage- $V_{oc}(V)$	25.24	25.31	25.38	25.45
Short Circuit Current- $I_{sc}(A)$	12.81	12.91	13.01	13.29
Maximum Power Voltage- $V_{MPP}(V)$	22.07	22.14	22.21	22.28
Maximum Power Current- $I_{MPP}(A)$	12.01	12.20	12.38	12.57

STC :Irradiance 1000w/m²,Cell Temperature 25°C *Mearsure tolerance:±3%

Electrical Data (NOCT)


MaximumPower- $P_{MAX}(Wp)^*$	188	192	195	199
Open Circuit Voltage- $V_{oc}(V)$	24.10	24.17	24.24	24.31
Short Circuit Current- $I_{sc}(A)$	9.84	10.04	10.24	10.43
Maximum Power Voltage- $V_{MPP}(V)$	20.60	20.67	20.74	20.81
Maximum Power Current- $I_{MPP}(A)$	9.11	9.30	9.48	9.66

NOCT:Irradiance at 800W/m²,Ambient Temperature 20°C,Wind Speed 1m/s

Mechanical Data

Panel Dimension(H/W/0)	1750×1150×7.1 mm
Weight	30kg
Cell Type	N-Type Monocrystalline
Cell Number	72 (36x2)
Front/Back Glass	3.2 mm+3.2 mm tempered glass
Transmittance	30%-40%
Junction Box	IP68 Rated
Output Cables	TÜV x4.0 mm ² ,(+)-400 mm,(-)-200 mm or customized lenght

Dimensions of PV Module(mm)



Length: ±2 mm
 Width: ±2 mm
 Height: ±1 mm
 Row Pitch: ±2 mm

Temperature Ratings

Nominal Operating Cell Temp.(NOCT)	45°C(±2°C)
Temperature Coefficient of P_{MAX}	-0.290%/°C
Temperature Coefficient of V_{oc}	-0.250%/°C
Temperature Coefficient of I_{sc}	+0.045%/°C

* Do not connect Fuse in Combiner Box with two or more strings in parallel connection

Packaging Configuration

Modules per box	30 pieces
Modules per 40'container	780 pieces

Maximum Ratings

Operational Temperature	-40~±85 °C
Front/Rear Side Load	5400/2400pa
Max Series Fuse Rating	25A
Max System Voltage	1500V (IEC)
Fire Rating	Class 1(UN19177)

Warranty

Product Workmanship Warranty	30 years
Output Power Warranty	30 years

